

UNCLASSIFIED

AD NUMBER

AD813438

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; APR 1967. Other requests shall be referred to Arnold Engineering Development Center, Arnold AFS, TN.

AUTHORITY

AEDC ltr 23 Jan 1975

THIS PAGE IS UNCLASSIFIED

AEDC-TR-67-61

ARCHIVE COPY
DO NOT LOAN

by 1



AERODYNAMIC CHARACTERISTICS OF PROPOSED SNAP-29 FUEL BLOCK CONFIGURATIONS AT MACH NUMBER 8

R. H. Burt and W. R. Martindale

ARO, Inc.

April 1967

This document has been approved for public release
its distribution is unlimited *per 35 letter
dated 23 January
75 signed W. H. H. J. Jr.
D. L. H.*

This document is subject to special export controls
and each transmittal to foreign governments or foreign
nationals may be made only with prior approval of
Atomic Energy Commission, Albuquerque Operations
Office, Albuquerque, New Mexico.

**VON KÁRMÁN GAS DYNAMICS FACILITY
ARNOLD ENGINEERING DEVELOPMENT CENTER
AIR FORCE SYSTEMS COMMAND
ARNOLD AIR FORCE STATION, TENNESSEE**

PROPERTY OF U. S. AIR FORCE
AEDC LIBRARY
AF 40(600)1200

AEDC TECHNICAL LIBRARY



5 0720 00031 4841

NOTICES

When U. S. Government drawings specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

AERODYNAMIC CHARACTERISTICS OF PROPOSED SNAP-29
FUEL BLOCK CONFIGURATIONS AT MACH NUMBER 8

R. H. Burt and W. R. Martindale
ARO, Inc.

This document has been approved for public release
its distribution is unlimited

*Rec AF letter
dated 23 January
75 signed William
O. Cole*

This document is subject to special export controls
and each transmittal to foreign governments or foreign
nationals may be made only with prior approval of
Atomic Energy Commission, Albuquerque Operations
Office, Albuquerque, New Mexico.

FOREWORD

The work reported herein was done at the request of the Atomic Energy Commission for the Martin Company, Baltimore Division, under Program Area 921D, AEC Activity Number 04-30-13-01. 2.

The test results presented herein were obtained by ARO, Inc. (a subsidiary of Sverdrup & Parcel and Associates, Inc.), contract operator of the Arnold Engineering Development Center (AEDC), Air Force Systems Command (AFSC), Arnold Air Force Station, Tennessee, under Contract AF40(600)-1200. The tests were conducted from January 9 to 13, 1967, under ARO Project No. VB1746, and the manuscript was submitted for publication on March 13, 1967.

Information in this report is embargoed under the Department of State International Traffic in Arms Regulations. This report may be released to foreign governments by departments or agencies of the U. S. Government subject to approval of Atomic Energy Commission, Albuquerque Operations Office, Albuquerque, New Mexico. Private individuals or firms require a Department of State export license.

This technical report has been reviewed and is approved.

James N. McCready
Major, USAF
AF Representative, VKF
Directorate of Test

Leonard T. Glaser
Colonel, USAF
Director of Test

ABSTRACT

Selected static-stability test results of five proposed SNAP-29 fuel block configurations are presented. Test configuration changes were made by varying the edge shape of the basic flat plate fuel block. Tests of 0.25- and 0.50-scale models were conducted at a nominal Mach number of 8, Reynolds number based on model length of 0.6×10^6 , and angles of attack from 0 to 90 deg. Results of model support interference studies employing oil flow, pressure distribution, and image-type force data techniques are presented.

CONTENTS

	<u>Page</u>
ABSTRACT	iii
NOMENCLATURE	vi
I. INTRODUCTION	1
II. APPARATUS	
2.1 Models and Support	1
2.2 Wind Tunnel	2
2.3 Instrumentation	2
III. PROCEDURE	
3.1 Test Conditions	3
3.2 Test Procedure	3
IV. RESULTS AND DISCUSSION	5
REFERENCES.	6

TABLE

I. Test Summary	4
---------------------------	---

APPENDIX
Illustrations

Figure

1. Model Details	
a. Force Models	9
b. Balance Attachment for the 0.50-Scale Force Models	10
c. Balance Attachments for the 0.25-Scale Force Models	12
d. 0.25-Scale Pressure Model	14
2. Schlieren Photographs	16
3. Axial-Pressure Distributions and Oil Flow Photographs for Configuration E ₁ , $\gamma = 0$	17
4. Effect of Balance Attachment Image, S ₁ ', on the Longitudinal Stability and Axial-Force Coefficients of Configuration E ₁ , $\gamma = 0$	18
5. Effect of Edge Shape on Longitudinal Stability and Axial-Force Coefficients, $\gamma = 0$, $\alpha = 0$ to 35 deg	19

<u>Figure</u>	<u>Page</u>
6. Longitudinal Stability and Axial-Force Coefficients for Configurations E ₁ and E ₂ , $\gamma = 0$, $\alpha = 0$ to 90 deg	20
7. Lift and Drag Characteristics of Configurations E ₁ and E ₂ , $\gamma = 0$, $\alpha = 0$ to 90 deg	21
8. Effect of Model Rotation on the Longitudinal Stability and Axial-Force Coefficients of Configuration E ₂ , $\alpha = 0$ to 35 deg	22
9. Lateral Stability and Rolling-Moment Coefficients for Configuration E ₂	23

NOMENCLATURE

CA	Axial-force coefficient, axial force/ $q_{\infty}S$
CD	Drag coefficient, $C_A \cos \alpha + C_N \sin \alpha$
CL	Lift coefficient, $C_N \cos \alpha - C_A \sin \alpha$
C _l	Rolling-moment coefficient, rolling moment/ $q_{\infty}S\ell$
C _m	Pitching-moment coefficient, pitching moment/ $q_{\infty}S\ell$
CN	Normal-force coefficient, normal force/ $q_{\infty}S$
C _n	Yawing-moment coefficient, yawing moment/ $q_{\infty}S\ell$
CY	Side-force coefficient, side force/ $q_{\infty}S$
ℓ	Model reference length (see Fig. 1a), in.
L/D	Lift-to-drag ratio
M	Mach number
p	Pressure, psia
q	Dynamic pressure, psi
Re	Unit Reynolds number, ft^{-1}
S	Model reference area (see Fig. 1a), in.^2
T	Temperature, °R
x	Distance from model leading edge (see Fig. 1d), in.
α	Angle of attack, deg
γ	Model rotation angle (see Figs. 1b and 1c), deg

SUBSCRIPTS

- o Tunnel stilling chamber conditions
- ∞ Free-stream conditions

SECTION I INTRODUCTION

Safety requirements dictate that the fuel block of the SNAP-29 nuclear generator remain intact during re-entry into the atmosphere and that an accurate prediction of its impact footprint be made. A trajectory analysis to determine if these requirements can be met requires the aerodynamic characteristics of the fuel block as inputs. The objective of the present test was to obtain the static-stability and axial-force characteristics of several fuel block configurations at Mach number 8.

The tests were conducted in the 50-in. hypersonic tunnel (Gas Dynamic Wind Tunnel, Hypersonic (B)) of the von Kármán Gas Dynamics Facility (VKF), AEDC. Testing was accomplished at unit Reynolds numbers of 0.42×10^6 and 0.84×10^6 per foot on 0.50- and 0.25-scale fuel block models, respectively. The angle-of-attack range investigated was from 0 to 90 deg at model rotation angles from 0 to 90 deg.

SECTION II APPARATUS

2.1 MODELS AND SUPPORT

A total of eight models of five configurations (Fig. 1a) were supplied by the Martin Company. These consisted of five 0.50-scale force models, each with a different edge shape, two 0.25-scale force models, and a 0.25-scale pressure model. All models were made of 17-4 PH stainless steel.

The 0.50-scale force models were attached to balance attachment S_1 (Fig. 1b) which enclosed a sting-mounted balance. The models were rotated relative to the balance attachment to provide various model rotation angles while maintaining a fixed balance orientation. A balance attachment image S_1' was provided for addition to the model lower surface during support interference studies. Bent stings of +12 and -12 deg were used with these models giving an angle-of-attack range of -20 to 35 deg.

The 0.25-scale force models were fastened to the balance by means of balance attachments S_2 and S_3 (Fig. 1c), the balance being enclosed by a sting-mounted windshield. These models were rotated relative to the balance attachments in a manner similar to the 0.050-scale models.

Balance attachments S₂ and S₃ were used in conjunction with a straight sting giving model angles of attack from 30 to 60 deg with S₂ and 60 to 90 deg with S₃.

The pressure model lee surface was instrumented with 55 orifices (Fig. 1d). Simulated balance attachments were provided for use in a study of support interference on model surface pressure distribution. The model was mounted on a bent sting and was pivoted to provide total prebend angles of 10, 30, 50, and 80 deg giving an angle-of-attack range from 0 to 90 deg. Another pivot was provided to give model rotation angles of 0 and 15 deg.

2.2 WIND TUNNEL

Tunnel B is a continuous, closed-circuit, variable density wind tunnel with an axisymmetric contoured nozzle and a 50-in. -diam test section. The tunnel operates at a nominal Mach number of 6 or 8 at stagnation pressures from 20 to 280 and from 50 to 900 psia, respectively, at stagnation temperatures up to 1350°R. The model may be injected into the tunnel for a test run and then retracted for model cooling or model changes without interrupting the tunnel flow. A description of the tunnel may be found in Ref. 1.

2.3 INSTRUMENTATION

2.3.1 Force

Model forces and moments were measured with a six-component, moment-type, strain-gage balance supplied and calibrated by VKF. Before the test, combined balance static loadings were applied, simulating the model loading range anticipated during the test. The uncertainties listed below correspond to the differences between the applied loads and the values calculated by the final data reduction balance equations.

<u>Balance Component</u>	<u>Design Load</u>	<u>Maximum Static Loads</u>	<u>Uncertainties</u>
Normal force, lb	±200	±100	±0.5
Pitching moment, in. -lb	±680	±150	±3.3
Side force, lb	±200	±50	±0.3
Yawing moment, in. -lb	±680	±75	±1.9
Rolling-moment, in. -lb	±100	±50	±1.9
Axial force, lb	±50	+130	±0.5

2.3.2 Pressure

Model surface pressures were measured with 15-psid transducers referenced to a near vacuum. From repeat calibrations, the estimated measurement precision was ± 0.003 psi or ± 0.5 percent, whichever was greater.

2.3.3 Flow Visualization

Model flow field schlieren photographs were obtained for all test conditions during the force tests. Figure 2 shows typical examples of these photographs.

Photographs of the surface flow patterns for selected conditions were obtained by spraying the pressure model with Zyglo Penetrant[®] and illuminating it with ultraviolet light during exposure to tunnel flow. A complete description of this technique is given in Ref. 2 and representative results are shown in Fig. 3.

SECTION III PROCEDURE

3.1 TEST CONDITIONS

A summary of test conditions is given below:

M_∞	$Re_\infty \times 10^{-6} \text{ ft}^{-1}$	$p_o, \text{ psia}$	$T_o, ^\circ\text{R}$	$p_\infty, \text{ psia}$	$q_\infty, \text{ psi}$
7.87	0.42	70	1170	0.008	0.35
7.91	0.84	160	1225	0.018	0.76

3.2 TEST PROCEDURE

The 0.50-scale models were tested at the low unit Reynolds number and the 0.25-scale models at the high unit Reynolds number thereby providing a constant Reynolds number based on model size. Because of model size, the 0.50-scale model tests were limited to a maximum angle of attack of 35 deg to prevent tunnel blocking. The 0.25-scale force models were tested at angles of attack from 30 to 90 deg, and the pressure model was tested at angles of attack from 0 to 90 deg. A complete summary of the test schedule is presented in Table I.

TABLE I
TEST SUMMARY

Force Tests

Configuration	Balance Attachment	γ , deg						
		0	15	30	45	60	75	90
E ₁	S ₁ , S ₂ , S ₃	A, B, C*, D*	A, B, C*	A, B, C*, D*	A, B, C*, D	A, B, C*, D	A, B, C*, D	A, B, C*, D
E ₁	S ₁ S ₁ '	A	A	A	A	A	A	A
E ₂	S ₁ , S ₂ , S ₃	A, B, C*, D	A, B, C	A, B, C*, D	A, B, C, D	A, B, C*, D	A, B, C, D	A, B, C, D
E ₂	S ₁ S ₁ '	A						
E ₃	S ₁	A, B			A, B			
E ₃	S ₁ S ₁ '	A						
E ₄	S ₁	A, B			A, B			
E ₄	S ₁ S ₁ '	A						
E ₅	S ₁	A, B			A, B			
E ₅	S ₁ S ₁ '	A			A			

A - $\alpha = -20$ to $+10$ deg, $Re_{\infty} = 0.42 \times 10^6$, ft^{-1} , 0.50-scale models

B - $\alpha = 5$ to 35 deg,

C - $\alpha = 30$ to 60 deg, $Re_{\infty} = 0.84 \times 10^6$, ft^{-1} , 0.25-scale models

D - $\alpha = 60$ to 90 deg,

*Also tested at $Re_{\infty} = 0.42 \times 10^6$, ft^{-1}

Pressure Tests

Configuration	Balance Attachment	α , deg												
		0	5	10	15	20	25	30	40	50	60	70	80	90
E ₁		E*	E	E	E*	E	E	E*	E	E*	E	F	F	F
E ₁	S ₁	E*	E	E	E*	E	E	E*	E	E*	E			
E ₁	S ₂					E	E	E*	E	E*	E			
E ₁	S ₃											F	F	F

E - $\gamma = 0$ and 15 deg

F - $\gamma = 0$ only

*Oil Flow Photographs Taken (Only at $\gamma = 0$ with S₁ Balance Attachment)

SECTION IV RESULTS AND DISCUSSION

Experimental determination of the aerodynamic characteristics of a flat plate configuration with an externally mounted balance presented the problem of assessing support interference. Three techniques were used in the present tests to obtain qualitative and quantitative support interference data. These consisted of model lee-side oil flow photographs and pressure distributions and an image technique of obtaining force data.

Examples of the oil flow photographs and pressure distributions are shown in Fig. 3. Diminishing influence of balance attachment S_1 on axial surface pressure distribution as angle of attack was increased from 0 to 15 deg was noted. A corresponding forward movement of flow separation from the model surface was indicated by the oil flow photographs. Balance attachments S_1 and S_2 produced negligible interference at 30-deg angle of attack (lower portion of Fig. 3), and similar results were obtained at higher angles of attack.

A quantitative evaluation of support interference effects on the force and moment coefficients was made by the image technique which is commonly used in low speed wind tunnel testing. Each 0.50-scale model was tested through a negative angle-of-attack range with and without balance attachment image S_1' (Fig. 1b) attached to the model. Typical results of these tests are shown in Fig. 4. An interference correction can be made by subtracting the difference in the coefficients at negative angle of attack from the corresponding coefficients obtained without the image at a positive angle of attack. As can be seen, this correction was small and limited to angles of attack less than 6 deg and was therefore neglected.

Longitudinal stability and axial-force coefficients for the five 0.50-scale configurations are shown in Fig. 5. Edge shape had a pronounced effect on C_m and trim angle. Stable trim points in the $10 < \alpha < 20$ -deg range were obtained for all configurations except E1. Axial-force coefficient increased with leading edge bluntness as expected.

Longitudinal stability and axial-force coefficients for Configurations E1 and E2 for $\alpha = 0$ to 90 deg are shown in Fig. 6. The sharp increase in C_m and corresponding decrease in C_A near $\alpha = 45$ deg may be attributed to shock detachment, i. e., the transition from a supersonic to a subsonic flow field in the region between the bow shock and the body. A similar phenomenon has been noted in the testing of blunt delta wings (Refs. 3 and 4).

Lift and drag coefficients and lift to drag ratio for Configurations E₁ and E₂ are shown in Fig. 7. Newtonian predictions for Configuration E₁ were obtained using the procedure illustrated in Ref. 5 and a Newtonian constant of 2. The agreement was fair except for C_D at high angles of attack and L/D at low angles of attack.


Configuration E₂ longitudinal stability and axial-force coefficients for model rotation angles from 0 to 45 deg are shown in Fig. 8. The change in effective model geometry resulting from model rotation reduced trim angle and axial-force coefficients. (Note that the axis system remained fixed as the model was rotated.) Rotation angles from 45 to 90 deg produced data essentially symmetric with the $\gamma = 0$ to 45-deg data and hence are not shown.

Lateral stability and rolling-moment coefficients for Configuration E₂ are shown in Fig. 9. The slight nonsymmetry about $\gamma = 45$ deg of the side force and rolling-moment data is attributed to the rectangular (rather than square) shape of the model.

REFERENCES

1. Test Facilities Handbook (6th Edition). "von Kármán Gas Dynamics Facility, Vol. 4." Arnold Engineering Development Center, November 1966.
2. Rhudy, R. W. "Flow Visualization Techniques for Use in Hypersonic Wind Tunnels." AEDC-TDR-64-108 (AD448116), October 1964.
3. Bernot, Peter T. "Pressure Distributions on Blunt Delta Wings at Angles of Attack Up to 90° and Mach Number of 6.85." NASA-TN-D-1954, July 1963.
4. Neal, Luther, Jr. and Fetterman, David E. "Control Surface Interaction Effects on Delta-Wing Windward Pressures at a Mach Number of 6.83 at High Angles of Attack." NASA-TN-D-2332, June 1964.
5. Clark, E. L. and Trimmer, L. L. "Equations and Charts for the Evaluation of the Hypersonic Characteristics of Lifting Configurations by Newtonian Theory." AEDC-TDR-64-25 (AD431848), March 1964.

**APPENDIX
ILLUSTRATIONS**




Configuration Dimension	E ₁ , 0.25	E ₁ , 0.50	E ₂ , 0.25	E ₂ , 0.50	E ₃ , 0.50	E ₄ , 0.50	E ₅ , 0.50
A	7.875	15.750	7.875	15.750	15.750	15.750	15.750
B	8.688	17.276	8.688	17.276	17.276	17.276	17.276
C	0.250	0.500	0.750	1.500	1.000	1.500	1.000
D	0.125	0.250					
E	0.087	0.174					
F			0.172	0.344			
G			0.750	1.500			
H			0.934	1.868			
I	0.174	0.348	0.174	0.348	0.348	0.348	0.348
S (Area)	72.22	288.9	95.04	380.2	342.2	380.2	342.2
J	8.125	16.25	9.375	18.75	17.75	18.75	17.75

All Dimensions in Inches


a. Force Models

Fig. 1 Model Details




b. Balance Attachment for the 0.50-Scale Force Models

Fig. 1 Continued



b. Concluded
Fig. 1 Continued





c. Balance Attachments for the 0.25-Scale Force Models

Fig. 1 Continued




c. Concluded
Fig. 1 Continued




All Dimensions in Inches

d. 0.25-Scale Pressure Model


Fig. 1 Continued




d. Concluded
Fig. 1 Concluded



$\alpha = 0$, 0.50-Scale Model



$\alpha = 43.3$ deg, 0.25-Scale Model



$\alpha = 90.1$ deg, 0.25-Scale Model

Configuration E_1 , $\gamma = 0$

Fig. 2 Schlieren Photographs




Fig. 3 Axial-Pressure Distributions and Oil Flow Photographs for Configuration E₁, $\gamma = 0$




Fig. 4 Effect of Balance Attachment Image, S_1' , on the Longitudinal Stability and Axial-Force Coefficients of Configuration E₁, $\gamma = 0$




Fig. 5 Effect of Edge Shape on Longitudinal Stability and Axial-Force Coefficients,
 $\gamma = 0$, $\alpha = 0$ to 35 deg




Fig. 6 Longitudinal Stability and Axial-Force Coefficients for Configurations E₁ and E₂,
 $\gamma = 0$, $\alpha = 0$ to 90 deg




Fig. 7 Lift and Drag Characteristics of Configurations E₁ and E₂, $\gamma = 0$, $\alpha = 0$ to 90°




Fig. 8 Effect of Model Rotation on the Longitudinal Stability and Axial-Force Coefficients of Configuration E₂, $\alpha = 0$ to 35 deg




Fig. 9 Lateral Stability and Rolling-Moment Coefficients for Configuration E₂

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) Arnold Engineering Development Center ARO, Inc., Operating Contractor Arnold Air Force Station, Tennessee		2a REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b GROUP N/A	
3 REPORT TITLE AERODYNAMIC CHARACTERISTICS OF PROPOSED SNAP-29 FUEL BLOCK CONFIGURATIONS AT MACH NUMBER 8			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) N/A			
5 AUTHOR(S) (Last name, first name, initial) Burt, R. H. and Martindale, W. R., ARO, Inc.			
6 REPORT DATE April 1967		7a TOTAL NO OF PAGES 31	7b NO OF REFS 5
8a CONTRACT OR GRANT NO AF 40(600)-1200		9a ORIGINATOR'S REPORT NUMBER(S) AEDC-TR-67-61	
b PROJECT NO		9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report) N/A	
c Program Area 921D			
d			
10 AVAILABILITY/LIMITATION NOTICES This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AEC, Albuquerque Operations Office, Albuquerque, N.M.			
11 SUPPLEMENTARY NOTES Available in DDC		12 SPONSORING MILITARY ACTIVITY Atomic Energy Commission, Albuquerque Operations Office, Albuquerque, N.M.	
13 ABSTRACT Selected static-stability test results of five proposed SNAP-29 fuel block configurations are presented. Test configuration changes were made by varying the edge shape of the basic flat plate fuel block. Tests of 0.25- and 0.50-scale models were conducted at a nominal Mach number of 8, Reynolds number based on model length of 0.6×10^6 , and angles of attack from 0 to 90 deg. Results of model support interference studies employing oil flow, pressure distribution, and image-type force data techniques are presented.			

This document has been approved for public release
its distribution is unlimited. Per AF Silver signed
23 January 75
William B. Cole

14

KEY WORDS

LINK A

LINK B

LINK C

ROLE

WT

ROLE

WT

ROLE

WT

hypersonic flow
 stability
 fuel block configurations
 pressure distribution tests
 flat plate

1. nuclear reactors - Snap 29
2. nuclear fuel blocks
3. "

15-14

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.